blueriiot



Technical Sheet

| Name | Blue Connect Plus |
|--------------------------------|--|
| Brand | Blueriiot |
| Manufacturer | Riiot Labs |
| Reference | 73661 |
| Dimensions | 253 mm x 96 mm |
| Weight | 714 g |
| Colors | Blue (plastic) Blue (rubber) |
| Box content (see below) | 1 x Blue Connect 1 x Rubber cap 1 x Fixing rope 1 x Blue Fit60 1 x Quick start guide |
| Protection Standard | IPx8 standard |
| Sensor | 4-in-1 sensor |
| | pH: Measuring range: 0 to 14 Accuracy: ± 0.1 Resolution: 0.1 |
| | Temperature: Measuring range: 5 to 50° C Accuracy: ± 0.2°C Resolution: 0.1° C |
| | Redox/ORP (gold): Measuring range: 0 to 999 mV Accuracy: ± 20mV Resolution: 1 mV |
| | Conductivity: Measuring range: 250 to 15,000 µS/cm Accuracy: ± 10 % Resolution: 1 µS/cm |
| Power supply | Replaceable Lithium Thionyl Chloride battery Battery lifetime: 24 months |
| Connectivity | Bluetooth Low Energy® (BLE), Sigfox® |
| Sigfox radio configuration | RC2, RC4 868 MHZ Check the countries compatibility: https://build.sigfox.com/ sigfox-radio-configurations-rc |
| Nominal voltage | 3,6 V |
| Warranties | Blue Connect: 2 years Sensor: 2 years Battery: 1 year |
| Certifications | FCC (blueriiot.com/legal) |
| Operating system (application) | iOS, Android (minimum required iOS 9.0 and Android 4.3) Bluetooth (minimum required 4.0 Bluetooth) |
| Application Languages | English, French, Spanish, Dutch, German, Italian, Portuguese, Czech, Swedish, Catalan, Polish. |

